

WALL-RECESSED ELECTRONIC SOAP DISPENSER EXCELLENCE



C620-E

Features:

- Wall-recessed electronic soap dispenser for washbasin with single cover plate.
- Heavy duty
- Frontal cover with clean surface in 6 mm solid brass. Handcrafted and chrome finished. No visible anti-vandal fixing screws
- Electronic circuit, soap tank with pump housed in a wall-recessed AISI 304 stainless steel 1mm-thick box
- Frontal cover in 2mm-thick AISI 304 stainless steel secured with 4 vandal-proof stainless steel screws
- Spout 75mm long
- Soap dispenser endowed with a 1 liter soap tank and a self-priming pump
- Adjustable soap dose
- Infrared electronic circuit with built-in dose-regulator potentiometer, an anti-drip system, a full/empty-tank led indicator, and a control for fast pump recharging
- Equipped with: Safety transformer, special funnel for soap tank refilling, with an inserted magnet to for fast recharging of the pump
- CE certified

Technical Specifications:

- Dose of soap:
- Supply:

Dependent on the density of the liquid and the regulation
Transformer 230/18Vca 6VA Class II IP65

Operational functions:

- Dose dispensing:

Immediate dose dispensing at hand detection and
equipped with an anti-drip sucking nozzle

WALL-RECESSED ELECTRONIC SOAP DISPENSER EXCELLENCE

C620T-E

Flush-mounted electronic soap dispenser with plate in chrome-plated polished brass. Chrome-plated spout made out of a full 10x40mm bar (length 70mm). Outer plate in one single block of chrome-plated polished solid brass to be fixed with hidden screws. Size:220x220mm.

Flush-mounted box in 1mm-thick stainless steel (size 190x185x85mm). Soap dispenser consisting of a 1-litre container in printed polyethylene made out of one single block fitted with full/empty probes, a self-priming pump suitable for soaps or disinfectants of different density whose quantity can be adjusted electronically, an infrared electronic circuit with incorporated anti-dripping system and two colored LEDs for monitoring the soap level in the container.

Fitted with a special funnel for soap refilling with a magnet on one side for refilling the pump rapidly once it is put near the photocells and a 230/18Vac safety transformer Class II, IP65. CE certified.

